PRO APCC TOP COAT

BRAND/PRODUCT NAME

PRO APCC TOP COAT

MANUFACTURER

PROTEC GREEN PTE LTD
No. 3 Sungei Kadut Street 6
Singapore 728851
Tel: 62695395 Fax 63671008

PRODUCT DESCRIPTION

PRO APCC TOP COAT is acrylic hybrid sealer top coat for Acrylic Polymer Cementitious Coating.

PRO APCC TOP COAT is used to enhance the abrasion resistance, slip resistance and stain resistance on the Acrylic Polymer Cementitious Coating. It also enhances the appearance of the cementitious coating making it slightly glossy.

ADVANTAGES

- Improve abrasion resistance
- Improve slip resistance
- Stain resistance properties
- Excellent water resistance properties
- Ready to use, easy to apply
- Enhance appearance

INSTALLATION

Surface Preparation

Surfaces receiving **PRO APCC TOP COAT** must be clean and free of dust, oil and all impurities/contaminants that might inhibit bonding.

Mixing

Use a slow speed mechanical mixer to mix 2 to 3 minutes until homogenous and lump free consistency. Use the mixture within the recommended pot life.

Application

Apply **PRO APCC TOP COAT** with a brush or roller after **PRO APCC - 2 Part** has cured.

Allow the first coat to dry to touch before applying the second coat in a perpendicular direction

Drying time

Dry to touch - 30 minutes to 1 hour
Light foot traffic - 1 hour to 4 hours

SHELF LIFE

Approximately 12 months in factory sealed packaging.

PRO APCC TOP COAT should be stored indoor.
*High humidity will reduce the shelf life of the product.

For further information, refer Safety Data Sheet.

TECHNICAL DATA

Performance Properties:

Appearance	White Liquid
Abrasion resistance @28 days After Thermal Aging BS EN 13892-4 2002	≤ 0.5mm ≤ 0.6mm
Slip resistance SS 485:2022	≥ 40
Shrinkage ASTM C531:2018 (ASTM G154:2000)	No cracks
Stain resistance HDB Method Adopted ISO 10545:14:2015	Class 5
Coverage	8-10m^2/kg

PACKAGING

PRO APCC TOP COAT comes in 5L, 20L pail.

PRO APCC-2 PART comes in 2 parts:
Part A: 25 Kg Powder (bagged)
Part B: 5 kg Liquid (bottled)

Sales and Technical Services

PROSPAQ GROUP PTE LTD
No. 3 Sungei Kadut Street 6
Singapore 728851
Tel: 6269 9532
Fax: 6367 1008
Email: sales@prospaq.com

The information in this catalogue is provided to the best of our knowledge from results gathered both internal and external credited laboratories. However, we have no control over site application, site conditions and workmanship of the applicator. We therefore will not accept any liability, either directly or indirectly arising from the misuse of these products or when the product is used not in accordance with any advice, specification, and recommendation of information given by us. The user is responsible for checking the suitability of these products for its intended use.